



GPS/GNSS NTP Time Servers

VCL-3048: NTP Time Server, IRIG-B

- Input: • GPS/GNSS
Outputs: • NTP • 1PPS • IRIG-B (Unmodulated BNC, RS-232, RS-485 / RS-422)
Power Supply: • 12V DC, 24V DC, 48V DC
Service Capacity: • Suitable for servicing up to 3000 NTP / SNTP requests per second.



VCL-2156: NTP, PRC (ITU-T G.811), IRIG-B, 1PPS

- Inputs: • GPS/GNSS, NTP
Outputs: • NTP • 2.048MHz • 10MHz • 1PPM/1PPH • 1PPS • ToD NMEA 0183 • IRIG-B (Unmodulated and Modulated)
Power Supply: • 24V DC, 48V DC, 110-220V DC, 110-240V AC, 1+1 Redundant PSU
Service Capacity: • Suitable for servicing up to 7500 NTP / SNTP requests per second.



VCL-2145-D / VCL-2145-DE: GPS/GNSS (1+1), PRC (G.811), PTP, NTP, IRIG-B

- Inputs: • GPS/GNSS (1+1), 10MHz, 2.048MHz, 2.048Mbit/s (E1)
Outputs: • NTP • PTP • 1.544Mbit/s (T1) / 2.048Mbit/s (E1) • 2.048MHz • 1/5/10MHz • 1PPS • IPPM • IRIG-B • ToD NMEA-0183
Power Supply: • 24V DC, 48V DC, 110-220V DC, 110-240V AC, 1+1 Redundant PSU
Service Capacity: • Suitable for servicing up to 8900 NTP / SNTP requests per second.



VCL-Mega, NTP Time Server

- Inputs: • GPS/GNSS, 1PPS, NTP Time Source
Outputs: • 16 x 1G/10G NTP Outputs
Power Supply: • 110~240VAC, 1+1 Redundant Hot-swappable PSU
Service Capacity: • Suitable for servicing up to 1 Million NTP / SNTP requests per second.



NTP Servers

Revision 1.7, January 20, 2025

© Copyright. All Rights Reserved.

U.S.A.

Valcomm Technologies Inc.
4000 Ponce de Leon Blvd.,
Suite 470, Coral Gables,
FL 33146, U.S.A.
E-mail: us@valiantcom.com

U.K.

Valiant Communications (UK) Ltd
Central House Rear Office
124 High Street, Hampton Hill
Middlesex, TW12 1NS, U.K.
E-mail: gb@valiantcom.com

INDIA

Valiant Communications Limited
71/1, Shivaji Marg,
New Delhi - 110015,
India
E-mail: mail@valiantcom.com

